

## Model : SPP-MTVW801

### Auto 8 in 1 out VGA Switch



- Support auto-scanning, and can set the interval time
- Support auto-detection
- Support 3.5mm audio
- Switching method: Press-key, IR remote, RS232
- Bandwidth 350MHz, resolution up to 2048 x 1536
- With 3.5 port to expand IR receive
- Support memory when the auto-scanning mode

#### Specifications

|                                   |   |
|-----------------------------------|---|
| Input port                        | 8 x HDB-15  |
| Output                            | 1 x HDB 15  |
| Output Resistance/ Magnitude      | 75Ω, RGB: 0.7Vp-p, HV: TIL level                      |
| Bandwidth (-3db)                  | 350MHz  |
| Resolution                        | Up to 2048 x 1536, DDC, DDC2, DDC2B (at the PNP port) |
| Horizontal frequency              | 30- 180Khz  |
| Vertical frequency                | 43-250Hz  |
| Output transmission distance      | ≤ 45m   |
| Input transmission distance       | ≤ 10m   |
| Isolation                         | -75 db(Mhz)   |
| Signal format                     | RGB stereo  |
| Audio format                      | 3.5mm audio   |
| Power                             | DV12V(500mA) Max consumption : 1.65W                  |
| Weight                            | 1.9kg   |
| Dimension                         | 44 x 15 x 4.2cm                                       |
| Operation Temperature             | -20-40 °C   |
| Operation Humidity                | 0-80%   |
| Gain rate                         | 0 db  |
| Frequency response                | 20Hz to 20Khz   |
| Total harmonic distortion + noise | 0.05% @1KHz   |
| CMRR                              | > 75db @ 20Hz to 20KHz                                |
| Resistance                        | > 10KΩ  |
| Max. Level                        | + 19.5 dbu  |
| DC compensation                   | Max. 5mV  |
| The range of auto-scanning time   | 0-59 s 0-99 minutes                                   |

**Connection Diagram:**

